NAME

gv_java - graph manipulation in java

SYNOPSIS

System.loadLibrary("gv");

USAGE

INTRODUCTION

gv_java is a dynamically loaded extension for **java** that provides access to the graph facilities of **graphviz.**

COMMANDS

New graphs

New empty graph

SWIGTYPE_p_Agraph_t **gv.graph** *(string name);*
SWIGTYPE_p_Agraph_t **gv.digraph** *(string name);*
SWIGTYPE_p_Agraph_t **gv.strictgraph** *(string name);*
SWIGTYPE_p_Agraph_t **gv.strictdigraph** *(string name);*

New graph from a dot-syntax string or file

SWIGTYPE_p_Agraph_t **gv.readstring** *(string string);*
SWIGTYPE_p_Agraph_t **gv.read** *(string filename);*
SWIGTYPE_p_Agraph_t **gv.read** *(SWIGTYPE_p_FILE f);*

Add new subgraph to existing graph

SWIGTYPE_p_Agraph_t **gv.graph** *(SWIGTYPE_p_Agraph_t g, string name);*

New nodes

Add new node to existing graph

SWIGTYPE_p_Agnode_t **gv.node** *(SWIGTYPE_p_Agraph_t g, string name);*

New edges

Add new edge between existing nodes

SWIGTYPE_p_Agedge_t **gv.edge** *(SWIGTYPE_p_Agnode_t t, SWIGTYPE_p_Agnode_t h);*

Add a new edge between an existing tail node, and a named head node which will be induced in the graph if it doesn't already exist

SWIGTYPE_p_Agedge_t **gv.edge** *(SWIGTYPE_p_Agnode_t t, string hname);*

Add a new edge between an existing head node, and a named tail node which will be induced in the graph if it doesn't already exist

SWIGTYPE_p_Agedge_t **gv.edge** *(string tname, SWIGTYPE_p_Agnode_t h);*

Add a new edge between named tail and head nodes which will be induced in the graph if they don't already exist

SWIGTYPE_p_Agedge_t **gv.edge** *(SWIGTYPE_p_Agraph_t g, string tname, string hname);*

Setting attribute values

Set value of named attribute of graph/node/edge - creating attribute if necessary

string **gv.setv** *(SWIGTYPE_p_Agraph_t g, string attr, string val);*
string **gv.setv** *(SWIGTYPE_p_Agnode_t n, string attr, string val);*
string **gv.setv** *(SWIGTYPE_p_Agedge_t e, string attr, string val);*

Set value of existing attribute of graph/node/edge (using attribute handle)

string **gv.setv** *(SWIGTYPE_p_Agraph_t g, SWIGTYPE_p_Agsym_t a, string val);*
string **gv.setv** *(SWIGTYPE_p_Agnode_t n, SWIGTYPE_p_Agsym_t a, string val);*
string **gv.setv** *(SWIGTYPE_p_Agedge_t e, SWIGTYPE_p_Agsym_t a, string val);*

Getting attribute values

Get value of named attribute of graph/node/edge

string **gv.getv** *(SWIGTYPE_p_Agraph_t g, string attr);*
string **gv.getv** *(SWIGTYPE_p_Agnode_t n, string attr);*
string **gv.getv** *(SWIGTYPE_p_Agedge_t e, string attr);*

Get value of attribute of graph/node/edge (using attribute handle)

string **gv.getv** *(SWIGTYPE_p_Agraph_t g, SWIGTYPE_p_Agsym_t a);*
string **gv.getv** *(SWIGTYPE_p_Agnode_t n, SWIGTYPE_p_Agsym_t a);*
string **gv.getv** *(SWIGTYPE_p_Agedge_t e, SWIGTYPE_p_Agsym_t a);*

Obtain names from handles

string **gv.nameof** *(SWIGTYPE_p_Agraph_t g);*
string **gv.nameof** *(SWIGTYPE_p_Agnode_t n);*
string **gv.nameof** *(SWIGTYPE_p_Agsym_t a);*

Find handles from names

SWIGTYPE_p_Agraph_t **gv.findsubg** *(SWIGTYPE_p_Agraph_t g, string name);*
SWIGTYPE_p_Agnode_t **gv.findnode** *(SWIGTYPE_p_Agraph_t g, string name);*
SWIGTYPE_p_Agedge_t **gv.findedge** *(SWIGTYPE_p_Agnode_t t, SWIGTYPE_p_Agnode_t h);*
SWIGTYPE_p_Agsym_t **gv.findattr** *(SWIGTYPE_p_Agraph_t g, string name);*
SWIGTYPE_p_Agsym_t **gv.findattr** *(SWIGTYPE_p_Agnode_t n, string name);*
SWIGTYPE_p_Agsym_t **gv.findattr** *(SWIGTYPE_p_Agedge_t e, string name);*

Misc graph navigators returning handles

SWIGTYPE_p_Agnode_t **gv.headof** *(SWIGTYPE_p_Agedge_t e);*
SWIGTYPE_p_Agnode_t **gv.tailof** *(SWIGTYPE_p_Agedge_t e);*
SWIGTYPE_p_Agraph_t **gv.graphof** *(SWIGTYPE_p_Agraph_t g);*
SWIGTYPE_p_Agraph_t **gv.graphof** *(SWIGTYPE_p_Agedge_t e);*
SWIGTYPE_p_Agraph_t **gv.graphof** *(SWIGTYPE_p_Agnode_t n);*
SWIGTYPE_p_Agraph_t **gv.rootof** *(SWIGTYPE_p_Agraph_t g);*

Obtain handles of proto node/edge for setting default attribute values

SWIGTYPE_p_Agnode_t **gv.protonode** *(SWIGTYPE_p_Agraph_t g);*
SWIGTYPE_p_Agedge_t **gv.protoedge** *(SWIGTYPE_p_Agraph_t g);*

Iterators

Iteration termination tests

bool **gv.ok** *(SWIGTYPE_p_Agraph_t g);*
bool **gv.ok** *(SWIGTYPE_p_Agnode_t n);*
bool **gv.ok** *(SWIGTYPE_p_Agedge_t e);*
bool **gv.ok** *(SWIGTYPE_p_Agsym_t a);*

Iterate over subgraphs of a graph

SWIGTYPE_p_Agraph_t **gv.firstsubg** *(SWIGTYPE_p_Agraph_t g);*
SWIGTYPE_p_Agraph_t **gv.nextsubg** *(SWIGTYPE_p_Agraph_t g, SWIGTYPE_p_Agraph_t sg);*

Iterate over supergraphs of a graph (obscure and rarely useful)

SWIGTYPE_p_Agraph_t **gv.firstsupg** *(SWIGTYPE_p_Agraph_t g);*
SWIGTYPE_p_Agraph_t **gv.nextsupg** *(SWIGTYPE_p_Agraph_t g, SWIGTYPE_p_Agraph_t sg);*

Iterate over edges of a graph

SWIGTYPE_p_Agedge_t **gv.firstedge** *(SWIGTYPE_p_Agraph_t g);*
SWIGTYPE_p_Agedge_t **gv.nextedge** *(SWIGTYPE_p_Agraph_t g, SWIGTYPE_p_Agedge_t e);*

Iterate over outedges of a graph

SWIGTYPE_p_Agedge_t **gv.firstout** *(SWIGTYPE_p_Agraph_t g);*
SWIGTYPE_p_Agedge_t **gv.nextout** *(SWIGTYPE_p_Agraph_t g, SWIGTYPE_p_Agedge_t e);*

Iterate over edges of a node
SWIGTYPE_p_Agedge_t **gv.firstedge** *(SWIGTYPE_p_Agnode_t n);*
SWIGTYPE_p_Agedge_t **gv.nextedge** *(SWIGTYPE_p_Agnode_t n, SWIGTYPE_p_Agedge_t e);*

Iterate over out-edges of a node
SWIGTYPE_p_Agedge_t **gv.firstout** *(SWIGTYPE_p_Agnode_t n);*
SWIGTYPE_p_Agedge_t **gv.nextout** *(SWIGTYPE_p_Agnode_t n, SWIGTYPE_p_Agedge_t e);*

Iterate over head nodes reachable from out-edges of a node
SWIGTYPE_p_Agnode_t **gv.firsthead** *(SWIGTYPE_p_Agnode_t n);*
SWIGTYPE_p_Agnode_t **gv.nexthead** *(SWIGTYPE_p_Agnode_t n, SWIGTYPE_p_Agnode_t h);*

Iterate over in-edges of a graph
SWIGTYPE_p_Agedge_t **gv.firstin** *(SWIGTYPE_p_Agraph_t g);*
SWIGTYPE_p_Agedge_t **gv.nextin** *(SWIGTYPE_p_Agnode_t n, SWIGTYPE_p_Agedge_t e);*

Iterate over in-edges of a node
SWIGTYPE_p_Agedge_t **gv.firstin** *(SWIGTYPE_p_Agnode_t n);*
SWIGTYPE_p_Agedge_t **gv.nextin** *(SWIGTYPE_p_Agraph_t g, SWIGTYPE_p_Agedge_t e);*

Iterate over tail nodes reachable from in-edges of a node
SWIGTYPE_p_Agnode_t **gv.firsttail** *(SWIGTYPE_p_Agnode_t n);*
SWIGTYPE_p_Agnode_t **gv.nexttail** *(SWIGTYPE_p_Agnode_t n, SWIGTYPE_p_Agnode_t t);*

Iterate over nodes of a graph
SWIGTYPE_p_Agnode_t **gv.firstnode** *(SWIGTYPE_p_Agraph_t g);*
SWIGTYPE_p_Agnode_t **gv.nextnode** *(SWIGTYPE_p_Agraph_t g, SWIGTYPE_p_Agnode_t n);*

Iterate over nodes of an edge
SWIGTYPE_p_Agnode_t **gv.firstnode** *(SWIGTYPE_p_Agedge_t e);*
SWIGTYPE_p_Agnode_t **gv.nextnode** *(SWIGTYPE_p_Agedge_t e, SWIGTYPE_p_Agnode_t n);*

Iterate over attributes of a graph
SWIGTYPE_p_Agsym_t **gv.firstattr** *(SWIGTYPE_p_Agraph_t g);*
SWIGTYPE_p_Agsym_t **gv.nextattr** *(SWIGTYPE_p_Agraph_t g, SWIGTYPE_p_Agsym_t a);*

Iterate over attributes of an edge
SWIGTYPE_p_Agsym_t **gv.firstattr** *(SWIGTYPE_p_Agedge_t e);*
SWIGTYPE_p_Agsym_t **gv.nextattr** *(SWIGTYPE_p_Agedge_t e, SWIGTYPE_p_Agsym_t a);*

Iterate over attributes of a node
SWIGTYPE_p_Agsym_t **gv.firstattr** *(SWIGTYPE_p_Agnode_t n);*
SWIGTYPE_p_Agsym_t **gv.nextattr** *(SWIGTYPE_p_Agnode_t n, SWIGTYPE_p_Agsym_t a);*

Remove graph objects
bool **gv.rm** *(SWIGTYPE_p_Agraph_t g);*
bool **gv.rm** *(SWIGTYPE_p_Agnode_t n);*
bool **gv.rm** *(SWIGTYPE_p_Agedge_t e);*

Layout

Annotate a graph with layout attributes and values using a specific layout engine
bool **gv.layout** *(SWIGTYPE_p_Agraph_t g, string engine);*

Render

Render a layout into attributes of the graph
bool **gv.render** *(SWIGTYPE_p_Agraph_t g);*

Render a layout to stdout
bool **gv.render** *(SWIGTYPE_p_Agraph_t g, string format);*

Render to an open file
bool **gv.render** *(SWIGTYPE_p_Agraph_t g, string format, SWIGTYPE_p_FILE fout);*

Render a layout to an unopened file by name
bool **gv.render** *(SWIGTYPE_p_Agraph_t g, string format, string filename);*

Render to a string result
string **gv.renderresult** *(SWIGTYPE_p_Agraph_t ing, string format);*
gv.renderresult *(SWIGTYPE_p_Agraph_t g, string format, string outdata);*

Render to an open channel
bool **gv.renderchannel** *(SWIGTYPE_p_Agraph_t g, string format, string channelname);*

Render a layout to a malloc'ed string, to be free'd by the caller

(deprecated - too easy to leak memory)

(still needed for "eval [gv::renderdata $G tk]")
string **gv.renderdata** *(SWIGTYPE_p_Agraph_t g, string format);*

Writing graph back to file
bool **gv.write** *(SWIGTYPE_p_Agraph_t g, string filename);*
bool **gv.write** *(SWIGTYPE_p_Agraph_t g, SWIGTYPE_p_FILE f);*

Graph transformation tools
bool **gv.tred** *(SWIGTYPE_p_Agraph_t g);*

KEYWORDS

graph, dot, neato, fdp, circo, twopi, java.